



1062-1063-Vibac Heavy Duty Tape

PRODUCT SPECIFICATION					
Description:	Vibac Heavy Duty Tape				
Available colours:	Transparent, Honey, White, Kraft				
Backing:	Bioriented polypropylene				
Adhesive:	Acrylic	Acrylic			
Code:	1062-1063				
TECHNICAL DATA					
Details	Method	u.m.	Typical Value	Tolerance	
Backing thickness		μm	32	+/- 5%	
Total thickness	AFERA 5006	μm	52	50 ÷ 54	
Longitudinal tensile strength	AFERA 5004	X`Kg/cm N/25mm	5,0 123	4,0 – 6,0 98 - 147	
Longitudinal elongation at breakage	AFERA 5004	%	160	110 - 210	
Adhesion to steel plate	AFERA 5001	g/cm N/25mm	250 6,1	≥ 200 ≥ 4,9	
Rolling ball tack	PSTC-6	Cm	1	≤ 3	
Shear on metal 50°C (1" x 1")	AFERA 5012	min	3000	> 1000	

Test methods are available on request. The above data refer only to average values based on tests carried out in Vibac laboratories. They are not valid as specifications.

APPLICATIONS:

Carton sealing adhesive tape suitable for the sealing of medium weight and heavy cartons.

- Silent unwinding •
- Available also in under surfaces printed version

GUARANTEE:

The product and its functionality is guaranteed for a period of 6 months from delivery date.



www.primepac.co.nz

- Sales@primepac.co.nz
- \bigcirc
- L31/61 Constellation Drive, Rosedale, Auckland