

Spot Marking Paint - Fluoro

Safety Data Sheet

SECTION 1: Product identifier 1.1. GHS Product identifier Product form : Mixture Product name : Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple) Product code : 7427, 7428, 7429, 7430, 7430, 7431, 7432, 7433 Date Issued : 9/02/2023 Validity Date : 9/02/2028

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use	: Use according to manufacturer's directions. Application is by spray atomisation from a hand held aerosol pack.
Restrictions on use	: Not to be used for any purpose other than the one the product was designed for

1.4. Details of manufacturer or importer

Signet Pty Ltd 56 Ingleston Rd WAKERLEY, QLD 4154 Australia T +61 (07) 3179 2100 sales@signet.net.au - www.signet.net.au

1.5. Emergency phone number

Emergency number

: Office hours: +61 (07) 3179 2100 Poisons Information Centre (24 h): 13 11 26

For more information about poisons or in case of poisoning, call the National Poisons Centre on **0800 764 766** A free 24/7 service for all New Zealanders

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)		
Aerosol, Category 1	H222 ; H229	
Serious eye damage/eye irritation, Category 2A	H319	

www.primepac.co.nz

sales@primepac.co.nz
L31/61 Constellation Drive, Rosedale, Auckland



2.2. GHS Label elements, including precautionary statements.

Hazard pictograms (GHS AU):



Flame Exclamation mark

Signal word (GHS AU) Contains	: Danger : Ethyl Acetate (< 30 %); Solvent naphtha (petroleum), light aromatic [contains less than 0,1 % w/w benzene] (< 10 %)
Hazard statements (GHS AU)	: H222 - Extremely flammable aerosol H229 - Pressurised container: May burst if heated H319 - Causes serious eye irritation
Precautionary statements (GHS AU)	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P251 - Do not pierce or burn, even after use. P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear eye protection, protective clothing, protective gloves. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents and container to an approved waste disposal plant.
Additional hazard statements (GHS AU)	: AUH044 - Risk of explosion if heated under confinement. Repeated exposure may cause skin dryness or cracking. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING CONTENT CAN BE HARMFUL OR FATAL

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

Name	CAS-No.	%
Ethyl Acetate	141-78-6	< 30
Limestone	1317-65-3	< 10

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation First-aid measures after skin contact First-aid measures after eye contact : Remove person to fresh air and keep comfortable for breathing. : Wash skin with plenty of water.

: Rinse immediately with plenty of water. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion

: Call a poison center or a doctor if you feel unwell.

www.primepac.co.nz

0800 277 772

] sales@primepac.co.nz

© L3

L31/61 Constellation Drive, Rosedale, Auckland

PRIMEPAC making it easy!

4.2. Symptoms caused by exposure	
Symptoms/effects after eye contact	: Eye irritation.
4.3. Medical attention and special treatment	
Other medical advice or treatment	: Treat symptomatically.
SECTION 5: Fire-fighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.Unsuitable extinguishing media are not known.
5.2. Specific hazards arising from the chemica	d.
Fire hazard Explosion hazard General measures	 : Extremely flammable aerosol. : Pressurised container: May burst if heated. : No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.
5.3. Special protective equipment and precaut	ions for fire-fighters
	Exercise caution when fighting any chemical fire. Keep upwind. Fight fire from safe distance and protected location. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting :	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental release measures	
6.1. Personal precautions, protective equipme	nt and emergency procedures
General measures :	No action shall be taken without appropriate training or involving any personal risk. Notify authorities if product enters sewers or public waters.
For non-emergency personnel	
Emergency procedures :	Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.





sales@primepac.co.nz L31/61 Constellation Drive, Rosedale, Auckland

PRIMEPAC making it easy!

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up	: Mechanically recover the product.
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including a	ny incompatibilities
Technical measures	: Does not require any specific or particular technical measures.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.
Information on mixed storage	: Store away from incompatible materials and products. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity.
Storage area	: Keep out of direct sunlight.
Special rules on packaging	: Position containers so that any labeling information is visible. Keep packaging closed when not in use. Check containers and packaging regularly for leaks and damage.
Packaging materials	: Keep only in original packaging.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards


Ethyl Acetate (141-78-6)	
Australia - Occupational Exposure Limits	
Local name	Ethyl acetate (Acetic acid ethyl ester; Acetic ester)
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)

Limestone (1317-65-3)	
Australia - Occupational Exposure Limits	
OES TWA [1]	10 mg/m ³
Remark (AU)	This value is for inhalable dust containing no asbestos and < 1% crystalline silica

8.2. Monitoring methods

Monitoring methods

: Workplace exposure - General requirements for the performance of procedures for the measurement of chemical agents. Gas detectors should be used when flammable gases/vapours may be released.



www.primepac.co.nz

Sales@primepac.co.nz

 \bigcirc

L31/61 Constellation Drive, Rosedale, Auckland



8.3. Engineering controls

Appropriate engineering controls: Ensure good ventilation of the work station. Use spark-/explosionproof
appliances and lighting system. Use grounded electrical/mechanical
equipment. Handle product within a closed system.8.4. Individual protection measures, such as personal protective equipment (PPE)Personal protective equipment: Personal protective equipment (PPE) must be suited to the nature of the
work and any hazard associated with the work as identified by the risk
assessment conducted. Avoid all unnecessary exposure. Ocular shower
with suitable liquid.
: Wear protective gloves

- Eye protection : We
- Skin and body protection
- Respiratory protection
- : Wear eye protection: Chemical goggles or safety glasses
- : Wear protective clothing: Long sleeved protective clothing
- : If mist is formed : Disposable half mask

Personal protective equipment symbol(s)




Consumer exposure controls

Other information

- : Personal protective equipment (PPE) is not required when handling individual retail pack.
- : PPE compliant to the recommended standards should be selected. The following Australian and New Zealand Standards will provide general advice regarding safety clothing and equipment: Respiratory equipment: AS/NZS 1715, Protective Gloves: AS 2161, Industrial Clothing: AS2919, Industrial Eye Protection: AS1336 and AS/NZS 1337, Occupational Protective Footwear: AS/NZS2210.

SECTION 9: Physical and chemical properties

Physical state Appearance Molecular mass Colour Odour Odour threshold pH pH solution Relative evaporation rate (butylacetate=1) Melting point / Freezing point Boiling point Flash point Auto-ignition temperature Decomposition temperature Flammability Vapour pressure Relative density Density	<pre>: Liquid : Aerosol. : Not applicable : Various colours : Not available : No data available : No data available : Not available : Not available : Melting point: Not available : Melting point: Not available : Not available : -81 °C (hydrocarbon propellant). : Not available : Not available : Not available : Not available : No data available : No data available : Vapour pressure: Not available : Relative vapour density at 20°C: Not available. (Air=1). : Density: ≈ 0.8 kg/l Relative density: (Water = 1) : Water imminisher</pre>
Solubility	: Water: immiscible
Partition coefficient	
n-octanol/water (Log Pow)	: Not available
Viscosity, kinematic	: Not available



sales@primepac.co.nz

L31/61 Constellation Drive, Rosedale, Auckland

making it easy!

Explosive properties Explosive limits Minimum ignition energy VOC content Fat solubility	: Pressurised : No data ava : No data ava : Not availabl : No data ava	ilable e
SECTION 10: Stability and reactivity		
Reactivity Chemical stability Possibility of hazardous reactions Conditions to avoid Incompatible materials Hazardous decomposition products	: Stable unde : No dangero : Avoid conta sources of ic : Strong acids : Under norm	ammable aerosol. Pressurised container: May burst if heated. r normal conditions. us reactions known under normal conditions of use. ct with hot surfaces. Heat. No flames, no sparks. Eliminate all gnition. 5. Strong bases. Strong oxidizers. al conditions of storage and use, hazardous decomposition buld not be produced.
SECTION 11: Toxicological information		
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	: Not classifie : Not classifie : Not classifie	ed
Ethyl Acetate (141-78-6)		
LD50 oral	5620 m	g/kg bodyweight
LD50 dermal	> 18000) mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	57700 r	ng/l
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity Reproductive toxicity STOT-single exposure	pH: Not app : Not classifie : Not classifie : Not classifie : Not classifie	licable ous eye irritation. licable d d d
Ethyl Acetate (141-78-6)		
STOT-single exposure	May caus	e drowsiness or dizziness.
STOT-repeated exposure Aspiration hazard	: Not classifie : Not classifie	
Spot Marking Paint - Fluoro Colours (Re	d, Blue, Oran	ge, Pink, Green, Yellow, Purple)
Vaporizer		Aerosol
Viscosity, kinematic		Not available
Ethyl Acetate (141-78-6)		
Animal studies and expert judgment for c	lassification	False
Acrylic Resin		
Animal studies and expert judgment for c	lassification	False

Sales@primepac.co.nz

- L31/61 Constellation Drive, Rosedale, Auckland

PRIMEPAC making it easy!

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity		
Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.	
Hazardous to the aquatic environment, short–term (acute)	: Not classified	
Hazardous to the aquatic environment, long—term (chronic)	: Not classified	
Ethyl Acetate (141-78-6)		
EC50 - Other aquatic organisms [1]	717 mg/l waterflea	
EC50 - Other aquatic organisms [2]	3300 mg/l	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)	
Partition coefficient n-octanol/water (Log Pow)	Not available
12.4 Mobility in soil	

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)	
Partition coefficient n-octanol/water (Log Pow)	Not available
12.5 Other adverse effects	

Ozone Other adverse effects : Not classified

: No additional information available

Spot Marking Paint - Fluoro Colours (Red, Blue, Orange, Pink, Green, Yellow, Purple)	
Fluorinated greenhouse gases	False
Ethyl Acetate (141-78-6)	
Fluorinated greenhouse gases	False
Limestone (1317-65-3)	
Fluorinated greenhouse gases	False



- \bigcirc
- 🖂 sales@primepac.co.nz L31/61 Constellation Drive, Rosedale, Auckland



SECTION 13: Disposal considerations

Waste treatment methods

Product/Packaging disposal recommendations

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : When totally empty, containers are recyclable like any other packing.

SECTION 14: Transport information

ADG	IMDG	ΙΑΤΑ
14.1. UN number		
1950	1950	1950
14.2. UN Proper Shipping Name		
AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		
2.1	2.1	2.1
14.4. Packing group		
Not applicable	Not applicable	Not applicable
4.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No

14.6 Special precautions for user	
Specific storage requirement Shock sensitivity	: No data available : No data available
14.7 Additional information	
Other information	: No supplementary information available
Transport by road and rail UN-No. (ADG) Special provision (ADG) Limited quantities (ADG) Excepted quantities (ADG) Packing instructions (ADG) Special packing provisions (ADG)	: 1950 : 63, 190, 277, 327, 344, 381 : See SP 277 : E0 : P207, LP200 : PP87, L2





Transport by sea UN-No. (IMDG) Special provisions (IMDG) Packing instructions (IMDG) Special packing provisions (IMDG) EmS-No. (Fire) EmS-No. (Spillage) Stowage category (IMDG) Stowage and handling (IMDG) Segregation (IMDG)	: 1950 : 63, 190, 277, 327, 344, 381, 959 : P207, LP200 : PP87, L2 : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE) : None : SW1, SW22 : SG69
Air transport UN-No. (IATA) PCA Excepted quantities (IATA) PCA Limited quantities (IATA) PCA limited quantity max net quantity (IATA) PCA packing instructions (IATA) PCA max net quantity (IATA) CAO packing instructions (IATA) CAO max net quantity (IATA) Special provisions (IATA) ERG code (IATA)	: 1950 : E0 : Y203 : 30kgG : 203 : 75kg : 203 : 150kg : A145, A167, A802 : 10L
14.8 Hazchem or Emergency Action Code	
Hazaham Cada	Notapplicable

Hazchem Code

: Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental regulations specific for the product in question

Australian Industrial Chemicals Introduction Scheme (AICIS)

Australian Inventory of Industrial Chemicals (AICIS Inventory) status : Listed

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Relevant Poisons Schedule number

: Unscheduled

15.2. International agreements

No additional information available





SECTION 16: Other information

Indication of changes:

Routine Review - No significant changes from previous issue.

Indicatio	on of changes		
Section	Changed Item	Change	Comments
	Supersedes	Modified	
	Date of revision	Modified	
	Issue date	Modified	
1.1	Product code	Modified	
2.1	Classification (GHS AU)	Modified	
2.2	Precautionary statements (GHS AU)	Modified	
2.2	Additional hazard statements (GHS AU)	Modified	
13.1	Product/Packaging disposal recommendations	Added	
13.1	Waste treatment methods	Modified	
16	Indication of changes	Modified	

Data sources	: Safe Work Australia - Code of Practice - Preparation of Safety Data Sheets for Hazardous Chemicals
	Safe Work Australia - Code of Practice - Labelling of Workplace Hazardous Chemicals Safe Work Australia - Workplace Exposure Standards for Airborne Contaminants Safe Work Australia - Hazardous Chemical Information System (HCIS)
	Australian Inventory of Industrial Chemicals (AICIS Inventory)
	Environmental Protection Authority - Hazardous Substances (Hazard Classification) Notice 2020
	Environmental Protection Authority - Hazardous Substances (Safety Data Sheets) Notice 2017
	Environmental Protection Authority - Hazardous Substances (Labelling) Notice 2017
	New Zealand - Chemical Classification and Information Database (CCID) New Zealand - Inventory of Chemicals (NZIoC)
	European Chemicals Agency (ECHA) - Ànnex VI (C&L Inventory)
	European Chemicals Agency (ECHA) - REACH Study Results
	European Chemicals Agency (ECHA) - REACH Registration Dossiers
	United Nations - Globally Harmonised System of Classification and Labelling of Chemicals (GHS)
	Uniform Scheduling of Medicines and Poisons (SUSMP)
	United Nations Recommendations on the Transport of Dangerous Goods (UNRTDG Model Regulation)
	Australian Dangerous Goods Code (ADG Code)
	International Air Transport Association Dangerous Goods Regulations (IATA DGR) International Maritime Dangerous Goods (IMDG Code).

Date of revision

: 12/07/2023







Classification		
	Aerosol 1	H222;H229
	Eye Irrit. 2A	H319

Full text of H-statements	text of H-statements	
Aerosol 1	Aerosol, Category 1	
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A	
Flam. Liq. 2	Flammable liquids, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	
H225	Highly flammable liquid and vapour	
H319	Causes serious eye irritation	
H336	May cause drowsiness or dizziness	

Safety Data Sheet (SDS), Australia

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.



 ô
 800 277 772
 www.primepac.co.nz



sales@primepac.co.nz L31/61 Constellation Drive, Rosedale, Auckland